



FEATURES

- Leads No. 20 Tinned Copper 1.5" long
- Coils Finished with VWI rated sleeving
- Nonstandard Values Available
- Saturation Current Lowers Inductance 5%
- Available Taped and Reeled for Auto Insertion

APPLICATIONS

- Switching power supplies
- SCR and Triac controls
- Switching regulators

Wilco Part Number	L uh +/- 15%	R.D.C. OHMS MAX.	Saturation Current (DC AMPS)	1 AMPS Suggested Rating	TEST FREQ.
SFB 39G	3.9	.019	7.3	1.28	1 KHz
SFB 47G	4.7	.020	6.3	1.28	1 KHz
SFB 56G	5.6	.020	5.6	1.28	1KHz
SFB 68G	6.8	.026	5.3	1.28	1 KHz
SFB 100	10	.033	4.1	1.28	1 KHz
SFB 150	12	.040	3.6	1.28	1 KHz
SFB 180	18	.044	3.0	1.28	1 KHz
SFB 220	22	.060	2.7	1.28	1 KHz
SFB 330	33	.075	2.2	1.008	1 KHz
SFB 470	47	.109	1.8	.804	1 KHz
SFB 560	56	.130	1.7	.800	1 KHz
SFB 680	68	.131	1.5	.804	1 KHz
SFB 101	100	.208	1.2	.632	1 KHz
SFB 151	150	.340	1.0	.508	1 KHz
SFB 221	220	.430	.86	.508	1 KHz
SFB 331	330	.665	.70	.400	1 KHz
SFB 471	470	1.15	.59	.315	1 KHz
SFB 561	560	1.27	.54	.315	1 KHz
SFB 681	680	1.61	.49	.250	1 KHz
SFB 821	820	1.96	.44	.200	1 KHz
SFB 102	1000	2.30	.40	.200	1 KHz
SFB 152	1500	3.45	.33	.158	1 KHz
SFB 222	2200	4.48	.27	.158	1 KHz
SFB 332	3300	6.56	.22	.125	1 KHz
SFB 472	4700	9.66	.18	.100	1 KHz
SFB 682	6800	16.3	.151	.082	1 KHz
SFB 103	10000	26.4	.125	.050	1 KHz
SFB 153	15000	42.5	.098	.039	1 KHz

Wilco Corporation

6451 Saguro Ct.
 Indianapolis, IN 46268
 Hotline 800•611•2343
 Fax 317•293•9462
 www.wilcocorp.com